

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE


[Membership](#) | [Publications/Services](#) | [Standards](#) | [Conferences](#) | [Careers/Jobs](#)
**IEEE Xplore®**  
 RELEASE 1.4

 Welcome  
 United States Patent and Trademark Office

[Help](#) | [FAQ](#) | [Terms](#) | [IEEE Peer Review](#)

Quick Links

» S

Welcome to IEEE Xplore®

[SEARCH RESULTS](#)[\[PDF Full-Text \(288 KB\)\]](#)[PREVIOUS](#)[NEXT](#)[DOWNLOAD CITATION](#)

- ☐ [Home](#)
- ☐ [What Can I Access?](#)
- ☐ [Log-out](#)

**Tables of Contents**

- ☐ [Journals & Magazines](#)
- ☐ [Conference Proceedings](#)
- ☐ [Standards](#)

**Search**

- ☐ [By Author](#)
- ☐ [Basic](#)
- ☐ [Advanced](#)

**Member Services**

- ☐ [Join IEEE](#)
- ☐ [Establish IEEE Web Account](#)
- ☐ [Access the IEEE Member Digital Library](#)

[Print Format](#)
**Integer lapped biorthogonal transform**

Zhong Guangjun Cheng Lizhi Chen Huowang

Sch. of Comput., Nat. Univ. of Defense Technol., Changsha;

*This paper appears in: Image Processing, 2001. Proceedings. 2001*

International Conference on

10/07/2001 -10/10/2001, 7-10 Oct 2001

Location: Thessaloniki, Greece

On page(s): 471-474 vol.2

7-10 Oct 2001

References Cited: 10

Number of Pages: 3 vol.(lxx+1133+1108+1110)

INSPEC Accession Number: 7219466

**Abstract:**

A type of lapped biorthogonal transform that can map integers to integers is considered. Based on the computational structure of the proposed lapped transform, an efficient multiplierless algorithm for the lapped biorthogonal transform (LBT), called integer lapped biorthogonal transform (IntLBT), is proposed. The proposed IntLBT is implemented by a series of dyadic lifting stages and provides fast, efficient computation of the transform coefficients as well as the ability to map integers to integers. Application of the novel IntLBT in lossy image coding gains very competitive results comparing to the performance of the more complex Cohen-Daubechies-Feauveau (CDF) 9/7-tap biorthogonal wavelet with irrational coefficients.

**Index Terms:**
[data compression](#) | [discrete cosine transforms](#) | [image coding](#) | [transform coding](#)
**Documents that cite this document**

Select link to view other documents in the database that cite this one.

[SEARCH RESULTS](#)[\[PDF Full-Text \(288 KB\)\]](#)[PREVIOUS](#)[NEXT](#)[DOWNLOAD CITATION](#)
[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#) | [Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Us](#) | [No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2002 IEEE — All rights reserved

# INTEGER LAPPED BIORTHOGONAL TRANSFORM

Zhong Guangjun, Cheng Lizhi and Chen Huowang

School of Computer, National University of Defence Technology

Changsha 410073, China

Email: gjzhwj@263.net, {gjzhong, lzchen}@nudt.edu.cn

## ABSTRACT

In this paper, a type of lapped biorthogonal transform that can map integers to integers is considered. Based on the computational structure of the proposed lapped transform, an efficient multiplierless algorithm for the lapped biorthogonal transform (LBT), called integer lapped biorthogonal transform (IntLBT), is proposed. The proposed IntLBT is implemented by a series of dyadic lifting steps, and provides fast, efficient computation of the transform coefficients as well as the ability to map integers to integers. Application of the novel IntLBT in lossy image coding gains very competitive results comparing to the performance of the much more complex Cohen-Daubechies-Feauveau (CDF) 9/7-tap biorthogonal wavelet with irrational coefficients.

## 1. INTRODUCTION

It is well known that the discrete cosine transform (DCT), which is used in the JPEG image compression standard, suffers especially at low bit rates from blocking artifacts. In order to overcome this drawback, many discrete transforms with overlapping bases have been found. For example, wavelet transform with long overlapping bases and lapped transforms [1] have elegantly solved the blocking effects problems. However, from the computational complexity viewpoints, the implementation of wavelet transform is generally much more complex than that of the DCT. The lapped biorthogonal transform (LBT) can indeed completely eliminate annoying blocking effects [2], the computational complexity required by LBT is also less than that needed by the wavelet transform, and in some cases the LBT's coding performance even surpasses that of the CDF 9/7-tap biorthogonal wavelet transform [3]. Nevertheless, unlike the DCT and wavelet transform, lapped transforms have not yet been widely adopted. As Tran lately pointed out that "one reason is that the

modest improvement in coding performance is not enough to justify the increase in computational complexity" [4]. In order to reduce the computational cost, Tran [4] suggested using lifting steps first introduced by Sweldens [5] for implementing LBT. However, the lapped transform introduced in [4] exists at least two drawbacks: (1) The DCT performed is still floating-point, so the floating-point multiplication is inevitable; (2) Since factor  $\sqrt{2}$  scaling the first oddly symmetric DCT coefficient is approximated by  $(25/16)$ , its inverse is also approximated by  $(16/25)$ , so the lapped transform does not map integers to integers. In this paper, we consider a family of lapped biorthogonal transforms by rescaling the first evenly symmetrical DCT coefficient by a factor of  $(1/\sqrt{2})$ . The proposed transform called IntLBT is very high efficient because a series of integer lifting steps is all that is required and the main computational process is based on integer DCT (IntDCT). When the IntLBT is applied to image coding, the performance of IntLBT coder is compared with the results obtained for the popular CDF 9/7-tap wavelet. Furthermore, the blocking artifacts that the traditional DCT possesses have been avoided completely.

## 2. INTEGER LAPPED BIORTHOGONAL TRANSFORM

In order to describe IntLBT, we first restate the definition of lapped biorthogonal transform (LBT) introduced by Malvar [2]. For simplicity, we illustrate the definition of the LBT by the flowgraph shown in Figure 1. It is easy observed that  $N$  is the samples, to minimize the transform's complexity, the LBT bases have length  $L = 2N$ , and the first oddly symmetric DCT coefficient (i.e., the first AC coefficient) is multiplied by a factor of  $\sqrt{2}$ . To achieve IntLBT, in this paper we propose to use factor  $(\sqrt{2}/2)$  rescaling the DC term of the intermediate DCT coefficient. Therefore, the proposed LBT can be




Fig.1 Flow chart of the LBT, with  $V_R$  defined in [1]




Fig.2 Flow chart of the new LBT


considered as a special case in [6] and the new developed LBT is illustrated as in Figure 2.

### 2.1. General IntLBT

Based on Figure 2, we now consider designing an efficient IntLBT of length- $N$ .

#### Step 1: IntDCT

Consider the adjacent two block transforms, and let the inputs of length- $N$  be  $X_1$  and  $X_2$ , respectively. Compute the IntDCT-II [7, 8] of the sequences  $X_1$  and  $X_2$ , and let the outputs be  $Y_1 = (y_0^{(1)}, y_1^{(1)}, \dots, y_{N-1}^{(1)})'$  and  $Y_2 = (y_0^{(2)}, y_1^{(2)}, \dots, y_{N-1}^{(2)})'$ . The flow chart is expressed into



#### Step 2: Integer butterfly operations

From Figure 2 we see that the integer butterfly operations can be decomposed into following two stages.

##### Stage 1: Integer butterfly operations inside each block

Inside each block transform of Figure 2, after DCT is implemented, the following butterfly operations are expressed into:

$$\begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} \frac{\sqrt{2}}{2} & 0 \\ 0 & \sqrt{2} \end{bmatrix} \begin{bmatrix} y_0^{(i)} \\ y_1^{(i)} \end{bmatrix} = R_{\frac{\pi}{4}} \begin{bmatrix} 2y_1^{(i)} \\ y_0^{(i)} \end{bmatrix}, \quad i=1,2, \quad (1)$$

and

$$\begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} y_{2k}^{(i)} \\ y_{2k+1}^{(i)} \end{bmatrix}, \quad i=1,2; \quad k=1,2,\dots,\frac{N}{2}-1. \quad (2)$$

Since  $\begin{bmatrix} 1 & 1 \\ -1 & 1 \end{bmatrix}$  maps integers to integers, to achieve integer transform we use integer transform matrix  $\bar{R}_{\frac{\pi}{4}}$  to

replace  $R_{\frac{\pi}{4}}$ , in this case we define

$$\begin{bmatrix} \bar{z}_0^{(i)} \\ \bar{z}_1^{(i)} \end{bmatrix} = \bar{R}_{\frac{\pi}{4}} \begin{bmatrix} 2y_1^{(i)} \\ y_0^{(i)} \end{bmatrix}, \quad i=1,2, \quad (3)$$

and

$$\begin{bmatrix} \bar{z}_{2k}^{(i)} \\ \bar{z}_{2k+1}^{(i)} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} y_{2k}^{(i)} \\ y_{2k+1}^{(i)} \end{bmatrix} \quad (4)$$

where  $i=1,2; k=1,2,\dots,\frac{N}{2}-1$ .

##### Stage 2: Integer butterfly operations between adjacent two block

From Figure 2 it is clear that after Stage 1 is completed, we need to implement butterfly operation between adjacent two transform blocks. This process itself maps integers to integers, and can be expressed as:

$$\begin{bmatrix} u_{2k} \\ u_{2k+1} \end{bmatrix} = \begin{bmatrix} 1 & 1 \\ 1 & -1 \end{bmatrix} \begin{bmatrix} \bar{z}_{2k}^{(1)} \\ \bar{z}_{2k}^{(2)} \end{bmatrix} \quad (5)$$

where  $k=0,1,\dots,\frac{N}{2}-1$ .

#### Step 3: Post integer rotations

Since  $V_R$  is a orthogonal transform matrix, it can be factorized into a number of plane rotations [4]. As in [4], we can use integer transform  $\bar{V}_R$  to approximate  $V_R$ . When  $\bar{V}_R$  is determined, post integer rotation is expressed by

$$[v_0, v_1, \dots, v_{\frac{N}{2}-1}]' = \bar{V}_R [u_1, u_3, \dots, u_{N-1}]'. \quad (6)$$

Therefore,  $[u_0, u_2, \dots, u_{N-2}, v_1, v_3, \dots, v_{\frac{N}{2}-1}]'$  is the desired IntLBT output.






Fig.3 Flow chart of 8x16 IntLBT, with BinDCT defined in [8] as BinDCT-B, where “<<” denotes left shifts, “>>” denotes right shifts

## 2.2. N=8 IntLBT

In practice, to reduce complexity, the length N is not too big. We consider N=8. Let

$$\bar{R}_{\pi} = \begin{bmatrix} 1 & -\frac{7}{16} \\ 0 & 1 \end{bmatrix} \begin{bmatrix} \frac{1}{16} & 0 \\ \frac{13}{16} & 1 \end{bmatrix} \begin{bmatrix} 1 & -\frac{7}{16} \\ 0 & 1 \end{bmatrix}, \quad (7)$$

and

$$\bar{R}_{0.13\pi} = \bar{R}_{0.16\pi} = \begin{bmatrix} 1 & 0 \\ \frac{1}{2} & 1 \end{bmatrix} \begin{bmatrix} 1 & -\frac{1}{2} \\ 0 & 1 \end{bmatrix}, \quad (8)$$

the detailed flow chart of 8x16 IntLBT is illustrated as Figure 3.

## 3. APPLICATION IN IMAGE CODING

In this section we show the experimental results, analyze and compare the performance of this IntLBT algorithm and other classical discrete transforms in image coding. To be fair, the same SPIHT's quantizer and entropy coder [9] are exploited to encode the coefficients of every transform. The transforms in comparison are 8x8 DCT, 8x8 binDCT [8], the new 8x16 IntLBT, and the popular CDF 9/7-tap wavelet with a six-level decomposition.

bpp	DCT	binDCT	CDF 9/7 wavelet	IntLBT
1	39.52	39.08	40.06	39.54
0.5	36.04	35.80	36.94	36.34
0.25	32.54	32.36	33.82	33.27
0.125	29.17	29.01	30.60	30.14
0.0625	26.28	26.25	27.65	27.13

Table 1: PSNR evaluation for Lena, in dB

bpp	DCT	binDCT	CDF 9/7 wavelet	IntLBT
1	35.86	35.52	36.24	35.90
0.5	32.39	32.21	32.79	32.59
0.25	29.59	29.63	30.34	29.94
0.125	27.65	27.45	28.22	28.00
0.0625	25.66	25.58	26.16	25.99

Table 2: PSNR evaluation for Goldhill, in dB

Bpp	DCT	binDCT	CDF 9/7 wavelet	IntLBT
1	35.96	35.42	36.29	36.97
0.5	30.90	30.57	31.24	31.94
0.25	27.03	26.79	27.43	28.18
0.125	24.27	24.05	24.44	25.27
0.0625	22.00	22.32	22.99	22.75

Table 3: PSNR evaluation for Barbara, in dB

Table 4: Comparison of transform Complexity (operations needed per transform coefficients)

	DCT	binDCT	CDF 9/7 wavelet	IntLBT
No. of integer additions	0	7.75	0	15
No. of integer shifts	0	3.5	0	6.75
No. of float additions	7.25	0	10.5	0
No. of float multiplications	3.25	0	7.875	0

In the three block transform cases, we use the modified zerotree structure in [10], where each block of transform coefficients are treated analogously to a full wavelet tree, and three more levels of integer 5/3 wavelet decomposition are employed to decorrelate the DC subband further. The objective coding results (PSNR in dB) for standard 512x512 Lena, Goldhill and Barbara test images are tabulated in Table 1~3.

It can be observed that the IntLBT outperforms DCT and binDCT, on three test images at all bit rates. Compared to CDF 9/7-tap wavelet transform, the IntLBT is also quite competitive. For example, for a smooth image such as Lena, the PSNR is about 0.5dB below.




Fig. 4 Quarter portions of reconstructed Barbara images at bpp=0.25

However, for more complex image in the most case the IntLBT even surpasses the CDF 9/7-tap wavelet. The PSNR improvement can reach as high as 0.83dB. Besides, the visual quality of its reconstructed images is also superior, as demonstrated in Figure 4, blocking effects is completely eliminated.

Another key advantage over CDF 9/7-tap wavelet transform is the low computational complexity of the IntLBT, the comparison of complexity between the IntLBT and other popular transforms is tabulated in Table 4. From the Table 4 we know that the computational complexity that needed by the proposed IntLBT is even less than that required by  $8 \times 8$  DCT because the floating-point multiplication and addition in the IntLBT is avoided completely.

#### 4. CONCLUSION

In this paper, we have presented a lapped biorthogonal transform that can map integer to integers. Using this lapped transform, a new family of integer lapped biorthogonal transform called IntLBT for image coding applications is also achieved. The IntLBT is found to have competitive performance compared to the much more complex CDF 9/7-tap wavelet transform. Simulation results also demonstrated that the IntLBT has significantly less blocking artifacts, higher peak signal to

noise ration, and better visual quality than the floating-point DCT. By using integer arithmetic operations, the implementation complexity of IntLBT is reduced considerably compared to the implementation of floating-point lapped biorthogonal transform.

#### 5. REFERENCES

- [1] H.S.Malvar et al. "The LOT: Transform coding without blocking effects," *IEEE Trans. Acoustics, Speech and Signal Processing*, 37(4), pp.553-559, 1989.
- [2] H.S.Malvar, "Biorthogonal and nonuniform lapped transforms for transform coding with reduced blocking and ringing artifacts," *IEEE Trans. Signal Processing*, vol.46(4), pp.1043-1053,1998.
- [3] M.Antonini, et al, "Image coding using wavelet transform," *IEEE Trans. on Image Processing*,1(2), pp.205 ~ 220, 1992.
- [4] T.D.Tran, "The LiftLT:fast-lapped transforms via lifting steps," *IEEE Trans. Signal Processing*, vol.7(6), pp.145-14148, 2000.
- [5] W.Sweldens, "The lifting scheme:a construction of second generation wavelets", *SIAM J. Math. Anal.*, 29 (2),pp.511-546, 1998.
- [6] S.C.Chan, "The generalized lapped transform(GLT) for subband coding applications," *Proc .IEEE Int. Conf. Acoust., Speech, Signal Processing*, Detroit, MI, May, 1995, pp.1508-1511.
- [7] L.Z.Cheng, et al, "Integer discrete cosine transform and its fast algorithm," *Electron. Lett.* 37(1), pp.64-65, 2001
- [8] T.D.Tran, "Fast multiplierless approximation of the DCT," *IEEE Signal Processing Letters*, vol. 7, pp.142-144, 2000.
- [9] A.Said and W.A.Pearlman, "New, fast, and efficient image codec based on set partitioning in hierarchical trees," *IEEE Trans. Circuits Syst. Video Technol.*, vol.6,pp.243-250,1996.
- [10] T.D.Tran. "A progressive transmission image coder using linear phase uniform filterbanks as block transform," *IEEE Trans. Image Processing*, 8(11), pp.1493-1507,1999.

[IEEE HOME](#) | [SEARCH IEEE](#) | [SHOP](#) | [WEB ACCOUNT](#) | [CONTACT IEEE](#)[Membership](#) | [Publications/Services](#) | [Standards](#) | [Conferences](#) | [Careers/Jobs](#)**IEEE Xplore<sup>®</sup>**  
RELEASE 1.4Welcome  
United States Patent and Trademark Office[Help](#) | [FAQ](#) | [Terms](#) | [IEEE Peer Review](#)[Quick Links](#)» [See](#)**Welcome to IEEE Xplore<sup>®</sup>**

- ☐ [Home](#)
- ☐ [What Can I Access?](#)
- ☐ [Log-out](#)

**Tables of Contents**

- ☐ [Journals & Magazines](#)
- ☐ [Conference Proceedings](#)
- ☐ [Standards](#)

**Search**

- ☐ [By Author](#)
- ☐ [Basic](#)
- ☐ [Advanced](#)

**Member Services**

- ☐ [Join IEEE](#)
- ☐ [Establish IEEE Web Account](#)
- ☐ [Access the IEEE Member Digital Library](#)

[Print Format](#)Your search matched **4** of **916175** documents.A maximum of **4** results are displayed, **15** to a page, sorted by **Relevance** in **descending** order.

You may refine your search by editing the current search expression or entering a new one in the text box.

Then click **Search Again**.**Results:**Journal or Magazine = **JNL** Conference = **CNF** Standard = **STD****1 Video compression using integer DCT***Ying-Jui Chen; Soontorn Oraitara; Truong Nguyen;*

Image Processing, 2000. Proceedings. 2000 International Conference on , Volu 2000

Page(s): 844 -847 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(500 KB\)\]](#) [IEEE CNF](#)**2 Integer DCTs and fast algorithms***Yonghong Zeng; Lizhi Cheng; Guoan Bi; Kot, A.C.;*

Signal Processing, IEEE Transactions on , Volume: 49 Issue: 11 , Nov 2001

Page(s): 2774 -2782

[\[Abstract\]](#) [\[PDF Full-Text \(201 KB\)\]](#) [IEEE JRN](#)**3 Integer lapped biorthogonal transform***Zhong Guangjun; Cheng Lizhi; Chen Huowang;*

Image Processing, 2001. Proceedings. 2001 International Conference on , Volu 7-10 Oct 2001

Page(s): 471 -474 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(288 KB\)\]](#) [IEEE CNF](#)**4 Integer discrete cosine transform and its fast algorithm***Li Zhi Cheng; Hui Xu; Yong Luo;*

Electronics Letters , Volume: 37 Issue: 1 , 4 Jan 2001

Page(s): 64 -65

## Welcome to IEEE Xplore®

- ☐ Home
- ☐ What Can I Access?
- ☐ Log-out

## Tables of Contents

- ☐ Journals & Magazines
- ☐ Conference Proceedings
- ☐ Standards

## Search

- ☐ By Author
- ☐ Basic
- ☐ Advanced

## Member Services

- ☐ Join IEEE
- ☐ Establish IEEE Web Account
- ☐ Access the IEEE Member Digital Library

 Print FormatYour search matched **4** of **903905** documents.A maximum of **4** results are displayed, **25** to a page, sorted by **Relevance** in **descending** order.

You may refine your search by editing the current search expression or entering a new one in the text box.

Then click **Search Again**.**Results:**Journal or Magazine = **JNL** Conference = **CNF** Standard = **STD****1 Integer DCTs and fast algorithms***Yonghong Zeng; Lizhi Cheng; Guoan Bi; Kot, A.C.;*

Signal Processing, IEEE Transactions on , Volume: 49 Issue: 11 , Nov 2001

Page(s): 2774 -2782

[\[Abstract\]](#) [\[PDF Full-Text \(201 KB\)\]](#) **IEEE JRN****2 Video compression using integer DCT***Ying-Jui Chen; Soontorn Oraitara; Truong Nguyen;*

Image Processing, 2000. Proceedings. 2000 International Conference on , Volume: 2 , 2000

Page(s): 844 -847 vol.2

[\[Abstract\]](#) [\[PDF Full-Text \(500 KB\)\]](#) **IEEE CNF****3 Integer discrete cosine transform and its fast algorithm***Li Zhi Cheng; Hui Xu; Yong Luo;*

Electronics Letters , Volume: 37 Issue: 1 , 4 Jan 2001

Page(s): 64 -65

[\[Abstract\]](#) [\[PDF Full-Text \(176 KB\)\]](#) **IEEE JRN****4 A new convolution structure for the realisation of the discrete cosine transform***Yuk-Hee Chan; Wan-Chi Siu;*

Circuits and Systems, 1990., IEEE International Symposium on , 1-3 May 1990

Page(s): 2373 -2376 vol.3

[\[Abstract\]](#) [\[PDF Full-Text \(316 KB\)\]](#) **IEEE CNF**

---

[Home](#) | [Log-out](#) | [Journals](#) | [Conference Proceedings](#) | [Standards](#) | [Search by Author](#) | [Basic Search](#) | [Advanced Search](#)  
[Join IEEE](#) | [Web Account](#) | [New this week](#) | [OPAC Linking Information](#) | [Your Feedback](#) | [Technical Support](#) | [Email Alerting](#)  
[No Robots Please](#) | [Release Notes](#) | [IEEE Online Publications](#) | [Help](#) | [FAQ](#) | [Terms](#) | [Back to Top](#)

Copyright © 2002 IEEE — All rights reserved